



## SUS 322 W ST 1800x600x500mm

|   |         |         | • • •   |         |         |         |         |         |
|---|---------|---------|---------|---------|---------|---------|---------|---------|
| 125 155<br>15 15<br>15 15<br>15<br>15<br>15<br>15<br>15<br>15<br>15<br>15<br>15<br>15<br>15<br>15<br>1 |         |         | • • •   |         |         |         |         |         |
| Name_Tag<br>Stainless Steel:  | 81 AISI |         |         |         |         |         |         |         |
| Handle<br>Stainless Steel:  | 81 AISI |         |         |         |         |         |         |         |
| Door RAL/NCS:   | 1015 Li | 1023 Tr | 2004 Pu | 3005 Wi | 3020 Tr | 5010 Ge | 5012 Li | 5018 Tu |

Each compartment is equipped with a self-adhesive name plate. Each compartment of a lockers with two doors in a column is equipped with a plastic bar and two hooks. Locked with 1-point cylinder lock. Door with registered industrial design of modern look. All elements made of 0.5 mm. Locker with 4 doors in 2 columns.

Diameter: 50,0 cm

Length: 60,0 cm

PRO

Height: 180,0 cm



AR/VR



WEBSITE

PROSAAS





エムの、つつ ど



AR/VR



WEBSITE

S PROSAAS